

Product Overview

The DSQ system was developed by Delphi Connection Systems to provide a reliable, standard terminal system that covers a broad range of applications at various OEMs. The system is available as either a sealed (1.5) or unsealed (1.5 and 2.8) system.


Market Segments

Automotive

Non-Automotive

Features and Benefits

- 2 piece contact system
- Terminal can be mated in two orientations
- 1.5 & 2.8 unsealed version available
- 1.5 sealed version available
- Secondary lock from 4 sides possible
- Tab size 1.5x0.6mm & 2.8x0.8mm



Application Guidelines

Crimp sizes:

DSQ 1.5

0.35-.0,5mm² 0.75-1.0mm²

Tin-plated

Max current capacity 15A

Temperature range -40°...135°

DSQ 2.8

0.5-1.0mm², 1.5-2.5mm²,

0.5+0.75mm², 0.5+0.5mm²

Tin-plated

Max current capacity 15A

Temperature range -40°...135°

Terminal Crimp Tooling

Delphi Global Crimp Tooling

PSG Hand Crimp Tool

NOTE: For correct reference of terminal part number to hand crimp tool information please contact your Power & Signal Group representative.

World Headquarters

4670 Richmond Road, Suite 120
Cleveland, OH 44128-5918
(216) 378-6600
(800) 722-5273

European Headquarters

Itterpark 11
D-40724 Hilden
Germany
+49 2103 250 0

Asian Headquarters

9/F, Phase 2, East Ocean Center
618 Yan An Road East
Shanghai 200001, PRC
+86 21 5306 1871



Double Spring Quadlock (DSQ)

Competitor Part Numbers

Delphi Part Numbers

DSQ 1.5

964261-3	6 000 05 14	26.591.201.701	15414399
964261-2	6 000 05 11	26.591.331.185	15396704
969005-3	6 000 06 14	26.596.201.702	15439754
969005-2	6 000 06 11	26.596.331.185	15408850
964263-3	6 000 05 34	26.592.201.702	15414401
964263-2	6 000 05 31	26.592.331.185	15396705
964274-3	6 000 06 34	26.041.201.702	15439756
964274-2	6 000 06 31	26.041.331.185	15408851
964348-2		26.593.331.185	15396706

DSQ 2.8

927774-6		28.003.201.178	15409037
		28.003.201.185	15409037
964284-2		28.004.201.178	15409039
		28.004.201.185	15409039
927773-3		26.354.201.185	15409041
927768-1		26.354.331.178	15409041

Terminals

DSQ 1.5

15414399	female, gold, 0.35-0.5
15396704	female, silver, 0.35-0.5
15439754	female, gold, 0.35-0.5, sealed
15408850	female, silver, 0.35-0.5, sealed
15414401	female, gold, 0.5-1.0
15396705	female, silver, 0.5-1.0
15439756	female, gold, 0.75-1.0, sealed
15408851	female, silver, 0.75-1.0, sealed
15396706	female, gold, double

DSQ 2.8

15409037	female, silver, 0.5+0.75, 2x0.5
15409039	female, silver, 0.5-1.0
15409041	female, silver, 1.5-2.5

For pricing and samples, contact your field sales representative. Or, visit us on the web at www.powerandsignal.de.

For drawings, data sheets or 3-D CAD models, call our engineering department at +49 2103 250 500

World Headquarters

4670 Richmond Road, Suite 120
Cleveland, OH 44128-5918
(216) 378-6600
(800) 722-5273

European Headquarters

Itterpark 11
D-40724 Hilden
Germany
+49 2103 250 0

Asian Headquarters

9/F, Phase 2, East Ocean Center
618 Yan An Road East
Shanghai 200001, PRC
+86 21 5306 1871