

115-06960

Article Number: 115-06960

Description: Arrowhead Push-Mount Cable Tie, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg



Base Data	Local Order Number	115-06960
	Type	RT50SFK
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Arrowhead is easy to install without the need for use with a tool.</li> <li>• Arrowhead gives a firm and secure fixing and can be used in multiple panel thicknesses.</li> <li>• Design provides low insertion and high extraction force ideal for the production environment.</li> </ul>
	Quantity Per	bag
	Product Description	Arrowhead Ties ensure a firm and secure fixing. The legs take up any variation in panel thickness enabling one part to suit many applications. These are quick and easy to install, and can be used with various surfaces such as sheet metal, wood, and cast iron.
	Short Description	Arrowhead Push-Mount Cable Tie, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		9.0"
Length L (Metric)		225mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		Yes
Width W (Imperial)		0.2"
Width W (Metric)		5.0mm
Width W2 (Imperial)		0.6"
Width W2 (Metric)		14.7mm
Height H (Imperial)		0.24"
Height H (Metric)		6mm

115-06960



Product Dimensions	Bundle Diameter Min. (Imperial)	0.24"
	Bundle Diameter Min. (Metric)	6.0mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.0mm
	Panel Thickness Max. (Imperial)	0.03"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.31"
	Panel Thickness Min. (Metric)	0.8mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.28"
	Mounting Hole Diameter D (Metric)	6.4 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.26"
	Mounting Hole Diameter D Max. (Imperial)	0.275"
	Thickness T (Imperial)	0.055"
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.93kg