

126-00001

# HellermannTyton

Article Number: 126-00001



Description: Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HS, Black, 500/bag

Base Data	Local Order Number	126-00001
	Type	T50SL5
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Wing design helps stabilize the tie in high vibration applications</li> <li>• Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.</li> <li>• Design of tie provides low insertion and high extraction force.</li> </ul>
	Quantity Per	pieces
	Product Description	Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.
	Short Description	Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HS, Black, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		222N
Length L (Imperial)		6.5"
Length L (Metric)		165mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.19"
Width W (Metric)		4.7mm
Width W2 (Imperial)		0.73"
Width W2 (Metric)		18.5mm
Bundle Diameter Min. (Imperial)		0.06"

126-00001

Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.3"
	Bundle Diameter Max. (Metric)	34.0mm
	Panel Thickness Max. (Imperial)	0.03"
	Panel Thickness Max. (Metric)	2.5mm
	Panel Thickness Min. (Imperial)	0.31"
	Panel Thickness Min. (Metric)	0.8mm
	Mounting Hole Diameter D (Imperial)	0.24 - 0.26"
	Mounting Hole Diameter D (Metric)	6.1 - 6.5 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.255"
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.2mm
	Material and Specifications	
Material		Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut		PA66HS
Material Cable Tie		Polyamide 6.6 heat stabilized (PA66HS)
Flammability		UL 94 V2
Operating Temperature		-40°F to +221°F (-40°C to +105°C)
REACH Compliant (Article 33)		Yes
ROHS Compliant		Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.6kg