

126-00044

Article Number: 126-00044

Description: Arrowhead Push-Mount Cable Tie, 6"L, 50lb, Panel Thickness .04"-.14", PA66, Natural, 1000/pkg



Base Data	
Local Order Number	126-00044
Type	T50SSF
Color	Natural (NA)
Features and benefits	<ul style="list-style-type: none"> <li>• Quick and easy mounting will save time.</li> <li>• Tie is releasable and reusable providing a cost savings.</li> <li>• Design provides low insertion and high extraction force.</li> </ul>
Quantity Per	bag
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Short Description	Arrowhead Push-Mount Cable Tie, 6"L, 50lb, Panel Thickness .04"-.14", PA66, Natural, 1000/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225N
Length L (Imperial)	6.25"
Length L (Metric)	159.0mm
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19"
Width W (Metric)	4.7mm
Height H (Imperial)	.30"
Height H (Metric)	7.50mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm

126-00044



Product Dimensions	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Panel Thickness Max. (Imperial)	0.14"
	Panel Thickness Max. (Metric)	3.56mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	1.0mm
	Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.28"
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987