

126-00081

Article Number: 126-00081



Description: Arrowhead Cable Tie, 6" Long, 50lb Tensile Strength, 6.5mm Round Hole, PA66HS Black, 500/Pkg

Base Data	
Local Order Number	126-00081
Type	T50SOSKSFT6.5E
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> <li>• Dome provides a tight, rattle-free installation.</li> <li>• Outside serrated strap has ribs designed for convoluted tubing.</li> <li>• Dome acts as a seal to keep out dust and liquid.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.
Short Description	Arrowhead Cable Tie, 6" Long, 50lb Tensile Strength, 6.5mm Round Hole, PA66HS Black, 500/Pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	180N
Length L (Imperial)	6.2"
Length L (Metric)	156.0mm
Fixation Method	Arrowhead (Small Mount)
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18"
Width W (Metric)	4.6mm
Bundle Diameter Min. (Imperial)	0.04"
Bundle Diameter Min. (Metric)	1.0mm
Bundle Diameter Max. (Imperial)	1.38"

126-00081



Product Dimensions	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.051"
	Panel Thickness Max. (Metric)	1.3mm
	Panel Thickness Min. (Imperial)	0.027"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Imperial)	0.25-0.26"
	Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
	Mounting Hole Diameter D Min. (Imperial)	0.248"
	Mounting Hole Diameter D Max. (Imperial)	0.264"
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.3kg