

126-00114

Article Number: 126-00114

Description: Arrowhead Push-Mount Cable Tie, 8.5"L, 50lb, Panel Thickness .07"-.12", PA66HIRHS, Natural, 500/pkg



Base Data	Local Order Number	126-00114
	Type	T50ROSAH6U
	Color	Natural (NA)
	Features and benefits	<ul style="list-style-type: none"> <li>• Arrowhead style mount provides low insertion and high extraction force.</li> <li>• Easy and quick insertion ideal for production environment.</li> <li>• Ties "click" into place upon final installation signaling installer insertion is complete.</li> </ul>
	Quantity Per	bag
	Product Description	Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.
	Short Description	Arrowhead Push-Mount Cable Tie, 8.5"L, 50lb, Panel Thickness .07"-.12", PA66HIRHS, Natural, 500/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225.0N
	Length L (Imperial)	8.5"
	Length L (Metric)	215.9mm
	Fixation Method	Arrowhead
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Outside Serrated
	Width W (Imperial)	0.2"
	Width W (Metric)	5.1mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.0mm
	Disc Diameter (Imperial)	0.63"
Disc Diameter (Metric)	15.9mm	

126-00114

**HellermannTyton**

Product Dimensions	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.07"
	Panel Thickness Min. (Metric)	1.8mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987