

126-00116

Article Number: 126-00116

Description: Wing Push-Mount Cable Tie, 8" Long, 50lb Tensile Strength, PA66HS, Black, 500/bag



Base Data	Local Order Number	126-00116
	Type	T50RSFM
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Wing design helps stabilize the tie in high-vibration applications. • Includes a ladder-type strap as opposed to a conventional serrated strap which provides the benefit of being extra flexible. • Tie is releasable and reusable giving additional use options.
	Quantity Per	bag
	Product Description	Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.
	Short Description	Wing Push-Mount Cable Tie, 8" Long, 50lb Tensile Strength, PA66HS, Black, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		8.0"
Length L (Metric)		205mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.6mm
Height H (Imperial)		.22"
Height H (Metric)		5.59mm
Bundle Diameter Min. (Imperial)		0.06"

126-00116



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.8"
	Bundle Diameter Max. (Metric)	45.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Imperial)	0.24 -0.26"
	Mounting Hole Diameter D (Metric)	6.0 - 6.6 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.26"
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987