

126-03100

Article Number: 126-03100



Description: Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag

Base Data	Local Order Number	126-03100
	Type	T50SOSSFT6.5E-MDL
	Color	Green (GN)
	Features and benefits	This tie has an arrowhead design of fixing which offers a positive, low push-in force and a high pull-out force. When combined with the optional foam rubber seal it offers additional protection against the ingress of moisture or dirt.
	Quantity Per	bag
	Product Description	Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.
	Short Description	Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		6.3"
Length L (Metric)		158.8mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Outside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.6mm
Height H (Imperial)		0.67"
Bundle Diameter Min. (Imperial)		0.06"
Bundle Diameter Min. (Metric)		1.5mm

126-03100



Product Dimensions	Bundle Diameter Max. (Imperial)	1.2"
	Bundle Diameter Max. (Metric)	30.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.07"
	Panel Thickness Max. (Metric)	1.8mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.26"
	Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.26"
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2kg