

155-32602



Article Number: 155-32602

Description: Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack

Base Data	Local Order Number	155-32602
	Type	FT6LG.M.St.Aufn.II
	Color	Black (BK)
	Features and benefits	Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges. HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.
	Quantity Per	bag
	Short Description	Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack
	Product Dimensions	Fixation Method
Slot Size (W2)		11.0mm
Disc Diameter (Imperial)		0.63"
Disc Diameter (Metric)		16mm
Panel Thickness Max. (Imperial)		0.2"
Panel Thickness Max. (Metric)		5.0mm
Panel Thickness Min. (Imperial)		0.03"
Panel Thickness Min. (Metric)		0.75mm
Mounting Hole Diameter D (Imperial)		0.26-0.28"
Mounting Hole Diameter D (Metric)		6.5 - 7.0 mm
Mounting Hole Diameter D Min. (Imperial)		0.26"
Mounting Hole Diameter D Max. (Imperial)		0.28"
Material and Specifications	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

155-32602

Material and Specifications	Material Shortcut	PA66HIRHS
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	0.8kg