

157-00120

Article Number: 157-00120



Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 25mm Offset, 9.1"L, 7.6–8.4 mm Hole, PA66HIRHS, Gy, 500/pkg

Base Data	
Local Order Number	157-00120
Type	T50ROSFT8SO25A
Color	Gray (GY)
Features and benefits	<ul style="list-style-type: none"> • Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas. • Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install. • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
Quantity Per	bag
Product Description	<p>HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.</p> <p>The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</p>
Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 25mm Offset, 9.1"L, 7.6–8.4 mm Hole, PA66HIRHS, Gy, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	222N
Length L (Imperial)	9.1"
Length L (Metric)	230.0mm
Identification Plate Position	none
Length L2 (Metric)	25.0mm
Releasable Closure	No
Width W (Imperial)	0.201"
Width W (Metric)	5.1mm
Height H (Imperial)	.90"
Height H (Metric)	22.30mm
Bundle Diameter Min. (Imperial)	0.06"

157-00120



Product Dimensions	Bundle Diameter Min. (Metric)	1.6mm
	Bundle Diameter Max. (Imperial)	1.97"
	Bundle Diameter Max. (Metric)	50.0mm
	Disc Diameter (Metric)	19.0mm
	Panel Thickness Max. (Imperial)	0.26"
	Panel Thickness Max. (Metric)	6.65mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.3"
	Mounting Hole Diameter D (Metric)	7.6 - 8.4 mm
	Mounting Hole Diameter D Min. (Imperial)	0.30"
	Mounting Hole Diameter D Max. (Imperial)	0.33"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 V2
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces